



**Thin-Film 980/1550 Wavelength Division Multiplexer**

[www.Optiworks.com](http://www.Optiworks.com)

This document proposes the specification of the Thin-Film Wavelength Division Multiplexer that transmits light at 1550 nm and reflects light at 980 nm.

## 1. Specifications

(All parameters are referenced without connectors. Typical connector loss 0.25 dB/pair)

Parameters		Specifications	Unit
Transmitted Band		1530-1610	nm
Reflected Band		965-995	nm
Passband Insertion Loss		$\leq 1.0$	dB
Reflected band Insertion Loss		$\leq 0.6$	dB
Insertion loss uniformity over Transmitted band		$\leq 0.3$	dB
Isolation in Transmission against Reflected Band		$\geq 30$	dB
Isolation in Reflection against Transmitted Band		$\geq 15$	dB
PDL		$\leq 0.1$	dB
PMD		$\leq 0.1$	ps
Return Loss		$\geq 50$	dB
Directivity		$\geq 55$	dB
Optical Power Handling		$> 500$	mW
Operating Temperature		0 to 70	°C
Storage Temperature		-40 to 85	°C
Fiber Type		SMF 28 at signal, HI 1060 at com and pump port	
Package Dimension (excluding strain relief)	Bare Fiber	$\phi 5.5 \times 35$ typical	mm
	900 $\mu$ m Loose Tube	$\phi 5.5 \times 40$ typical	

**2. Part number of WDM**

W	M	M									N			
---	---	---	--	--	--	--	--	--	--	--	---	--	--	--



**3. size reference**

NA

**4. RoHS appliance. GR-1209-Core, GR-1221-Core Generic Requirement and test standard.**

Disclaimer: INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH OPTIWORKS PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN OPTIWORKS TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, OPTIWORKS ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL OPTIWORKS BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS AND PROFITS,

**BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT.** Optiworks makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Unless specifically provided otherwise, Optiworks products are not intended, authorized, or warranted for use as components in medical applications, or applications intended to support or sustain life.

“Optiworks” and the Optiworks logo are registered trademarks of Optiworks Technologies Co., Ltd. Other names, terms and product names may be trademarks of others.

© 2016 Optiworks Technologies Co., Ltd. All rights reserved.

**Optiworks Technologies Co., Ltd.**

USA

OptiWorks, Inc. 47211 Bayside Pkwy.

Fremont, CA 94538

510-770-8266/510-770-8291

[sales@optiworks.com](mailto:sales@optiworks.com)

**China - Kunshan**

Optiworks(Kunshan)Co.,Ltd.

NO.168Nanhe Road, ETDZ

Kunshan 215300. PRC

Tel: +86 (512) 57630880-23305

[contact@optiworks.com](mailto:contact@optiworks.com)

China - Shanghai

Optiworks(Shanghai)Co.,Ltd.

Room 810-811, Changchun Business Building No.953QinZhou North Road.

Shanghai, 200233 PRC

Tel: +86 (21) 6485-8787

[contact@optiworks.com](mailto:contact@optiworks.com)